

Butler

Airdraulic

The Best Tyre-changer in the World *

- Original bead loosener (patented)
- Safely handles ultra low profiles tyres
- Approved for "EMT", "PAX" and "CSR" tyres**
- Patented plastic demount head: works in contact with the rim

* Winner of two international award in USA and New Zealand



** CSR is a Continental trade mark
EMT is a Goodyear trade mark
PAX is a Michelin trade mark

Airdraulic

TOP SAFETY FOR EVERY TYRE AND RIM

The Airdraulic is the top of the Butler passenger tyre changer range.

The Airdraulic has already become an international standard. Its hydraulic bead loosener permits the user to handle every kind of tough wheel without any damage.

Its **exclusive mounting head** (synthetic material) can ride closer than any steel head, reducing stress on beads on low profile tyres. Airdraulic is completely air powered: no need for any electric connection. Its **multi-piston air motor** generates high torque and a 15rpm speed.

The innovative "tulip" clamping system allows a perfect inner and outer clamping without the "launch pad" effect of the traditional table top design. The ergonomic position of the wheel is granted by a spring loaded centering device that allows you to work at the desired height.



THE LATEST VERSION

The latest version of the Airdraulic is called "**EVO SERIES**". On it several innovations are implemented. The motor, brakes and arms, **are all sealed by a rubber protection**.

The jaws are completely rubber coated and they can be easily removed before the inner clamping.

The rubber covered wheel support plate can be changed when worn out by means of four screws.

The Airdraulic F.I. is equipped with a tubeless inflating device



STANDARD EQUIPMENT

- Air drier/Oiler assembly
- Bead lever
- Extra Mounting head

OPTIONAL ACCESSORIES

- Patented H.M. (half moon) Tyre bead lever
- Bead depressor
- Mounting/dismounting paste
- Special brush for paste

TECNICAL DATA

<i>Motor speed</i>	15 rpm
<i>Recommended Air Supply</i>	10 bar/145 psi
<i>Max. wheel diameter</i>	40"
<i>Max. bead loosener opening</i>	490 mm (19")
<i>Inner clamping</i>	10" - 23"
<i>Outer clamping</i>	8" - 22"
<i>Bead loosener Power (each roller)</i>	2000 kg (4389lbs)
<i>Noise level</i>	<72 dB

DIMENSIONS & WEIGHTS

<i>Minimum Height</i>	1600 mm (63")
<i>Maximum Height</i>	1830 mm (72")
<i>Length</i>	1100 mm (43")
<i>Width</i>	1100 mm (43")
<i>Weight without tubeless inflator</i>	206 kg (454 lbs)
<i>Weight with tubeless inflator</i>	218 kg (481 lbs)

Distributor:



Butler

Butler Engineering & Marketing S.r.l.
Via Balduina 5/7 - 42010 Rio Saliceto (RE) ITALY
Ph. ++39.522.647911 - Fax ++39.522.649760
www.butler.it - info@butler.it